

Unifi G5 Bullet



Next-gen indoor/outdoor 2K HD PoE Camera.

- 2K (4MP) video resolution
- Flexible 3-axis adjust mount
- 9 m (30 ft) IR night vision
- AI event detections
- Record audio with an integrated microphone
- Connect and power using PoE
- Weatherproof (outdoor exposed)



| Mechanical | |
|--------------------|--|
| Dimensions | Without mount: Ø75.5 x 74.4 mm (Ø3 x 2.9") With mount: Ø75.5 x 150 mm (Ø3 x 5.9") |
| Weight | Without mount: 225 g (8 oz) With mount: 315 g (11.1 oz) |
| Enclosure material | Polycarbonate, aluminum alloy |
| Mount material | Wall mount: aluminum alloy, polycarbonate Pole mount: aluminum alloy |
| Weatherproofing | IPX4 |
| Resistance | IK04 |

| Optics | |
|------------|--|
| Sensor | 5MP CMOS |
| Lens | Fixed focal length |
| View angle | H: 84.4°, V: 45.4°, D: 99.8° |
| Night mode | Built-in IR LED illumination and IR cut filter |

| Video | |
|-----------------|--|
| Resolution | 4MP 2688 x 1512 (16:9) |
| Max. frame rate | 30 FPS |
| Image settings | Color, brightness, sharpness, contrast, white balance, exposure control, 2DNR, 3DNR, NR by motion, masking, text overlay |

| System | |
|-------------------------|--------------------------------------|
| Processor | Dual-core Arm® Cortex®-A7 based chip |
| Networking interface | 10/100 MbE RJ45 port |
| Max. power consumption | 4W |
| Power method | PoE |
| Supported voltage range | 37—57V DC |
| Button | Factory reset |
| Mounting | Wall, pole mount |

System

| | |
|-------------------------------|-----------------------------|
| Ambient operating temperature | -20 to 40° C (-4 to 104° F) |
| Ambient operating humidity | 0 to 90% noncondensing |
| Certifications | FCC, IC, CE |

Audio

| | |
|------------|-----------------------|
| Microphone | Yes (Can be disabled) |
|------------|-----------------------|

Software

| | |
|-----------------|---|
| Web application | UniFi Protect: Version 2.2.7 or 2.7.28 and later |
| Mobile app | UniFi Protect iOS™ and Android™: Version 1.10.0 and later |