

Yealink SIP T73W

Multifunctional SIP Phone, Excellent Voice Communication

Yealink



The T73W IP phone is an all-in-one business device offering high-quality voice communication and extended features. Its Hall switch technology helps create a quieter office environment, while the redesigned, slimmer look matches modern design standards. It supports 12 SIP accounts, a 2.8-inch color display with backlight, and the EXP55 expansion station. With Yealink's HD voice technology, it delivers clear audio and fast call response. Built-in Bluetooth

5.0 and dual-band Wi-Fi 6 (2.4/5 GHz) ensure modern wireless connectivity. A USB port enables headset use and call recording. Security is enhanced through TEE hardware encryption, improving both safety and performance. As part of the T7X series, it integrates with the Yealink ecosystem and supports headset configuration, updates, and intelligent switching via wear detection.

Key Features and Benefits:

- 2.8" 320x240 pixel display with backlight
- TEE hardware encryption solution
- Dual system function
- T7X Auto-P template unified
- Unified firmware for T7X series (T73U, T73W, T74U, T74W, T77U), T85W, and T87W
- Up to 12 SIP accounts
- PoE support
- Headset, EHS support
- Built-in Bluetooth, Wi-Fi
- Supports color-screen expansion modules
- Stand with 2 adjustable angles
- Wall mountable
- Handset with hall switch

Audio Features

- HD voice: HD handset, HD speaker
- Hearing aid compatible (HAC) handset
- Acoustic Shield
- Smart Noise Filtering
- Audio codec: AMR-WB (optional), G.722
- Narrowband codec: AMR-NB (optional), PCMU (G.711μ), PCMA (G.711A), G.723.1, G.729, G.729A, G.729B, G.729AB, G.726,

iLBC

- DTMF: In-band, Out-of-band (RFC 2833) and SIP INFO
- Full-duplex hands-free speakerphone with AEC
- VAD, CNG, AEC, PLC, AIB, AGC

User interface

- LCD screen

- 2.8-inch 320x240 resolution screen
- Support wallpaper and screen saver
- Incoming calls and unread message indicator lights
- Intuitive user interface
- Support multi-language operation interface
- Caller ID display of name, number, and photo
- Supports both dark and light themes

Phone Features

- 12 VoIP accounts
- One-touch speed dial, hotline, mute, DND
- Call hold, call forward, call waiting, call transfer
- Group listening
- Emergency call
- Redial, call return, auto answer
- 5-way conferencing
- Direct IP call without SIP proxy
- Ring tone selection/import/delete
- Set date time manually or automatically
- Dial plan, action URL/URI
- XML Browser, XML Push
- RTCP-XR (RFC3611)
- Custom DSS Key
- Accessibility features

Directory

- Local phonebook up to 1000 entries
- Blocklist
- XML/LDAP remote phonebook
- Google Contacts
- Smart dialing
- Contacts search/import/export
- Call history: All records/dialed/received/missed/forwarded calls

IP-PBX Features

- Busy Lamp Field (BLF), Bridged Line Appearance (BLA)
- Anonymous call, anonymous call rejection
- Message Waiting Indicator (MWI)
- Voice messages, call parking
- Call pickup, intercom, multicast
- Music on hold
- Call recording, mobile office, chief assistant
- Server-based recording function
- Visual mailbox user interface

Display and Indicator

- LED for call and message waiting indication
- Account status information red and green dual color indicator light
- Intuitive user interface with icons and soft keys
- Multilingual user interface
- Caller ID with name and number
- Screensaver
- Power saving

Feature keys

- 8 linekeys with LED keys (up to 40 dsskeys, 5 pages)
- 4 touch buttons: message, headset, mute, pagination(mute/headset/pagination button with indicator light)
- 4 function keys: call hold, call transfer, redial, hands-free
- 2 volume control keys
- 6 navigation keys

Interface

- Dual Gigabit Ethernet ports
- 1 x USB 2.0 interface (phone side):
 - - USB flash drive
 - - Connecting a USB headset
 - - Connecting to the color screen expansion station
 - - Wireless Headset Adapter EHS40
- 1 x security keyhole
- 1 x RJ9 (4P4C) handset interface
- 1 x RJ9 (4P4C) headset jack
- 1 x 5V power port
- USB interface (compatible with 2.0):
 - - Support Yealink Bluetooth headsets via BT51
 - - Supports connecting Yealink Bluetooth headset BH71/BH71 Workstation/BH71 Workstation Pro/BH72/BH76 via BT51
 - - USB Recording
 - - USB Headset
 - - Expansion module EXP55, can support up to 3 color screen expansion module cascaded
 - - Wireless Headset Adapter EHS40
- Support USB or Bluetooth connection to Yealink CP900/CP700 and UH38, USB connection to UH34/UH36/UH37:
 - - Basic functions: answer/end/mute call
 - - Advanced functions: sound quality optimization/redial/call hold/volume adjustment two-way synchronization/multi-way call control

Management

- Configuration: browser/phone/auto-provision
- Auto provision via FTP/TFTP/HTTP/HTTPS for mass deployment
- Auto-provision with PnP
- Broadsoft device management
- Zero-Sp-Touch, TR-069

- Phone lock for personal privacy protection
- Reset to factory, reboot
- Package tracing export, system log
- Support Yealink Device Management Platform (YDMP/YMCS)

Network and Security

- Built-in Dual-Band Wi-Fi:
 - - Network standard: IEEE802.11a/b/g/n/ac/ax
 - - Frequency band: 2.4GHz/5.0GHz
- Built-in Bluetooth 5.0:
 - - Connecting Bluetooth headset
 - - Connect your phone
 - - Connect headset and phone at the same time
 - - Connect to PC as PC peripheral
- IPv3/IPv6
- SIP v1 (RFC2543), v2 (RFC3261)
- Call server redundancy supported
- NAT traversal: STUN mode
- Proxy mode and peer-to-peer SIP link mode
- IP assignment: static/DHCP
- HTTP/HTTPS web server
- Time and date synchronization using SNTP
- UDP/TCP/DNS-SRV(RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP
- Support SRTP protocol
- Transport Layer Security (TLS 1.3)
- HTTPS certificate manager
- AES encryption for configuration file (AES256)
- Supported authentication mechanisms: MD5/SHA1/SHA224/SHA256/SHA384/SHA512
- OpenVPN, IEEE802.1X, L2TP VPN
- LLDP/CDP/DHCP VLAN, ICE
- WPA2/WPA3
- Secure boot
- GARP (Generic Attribute Registration Protocol)
- TEE hardware encryption solution

Other Physical Features

- Operating environment humidity: 4% - 90%
- Operating temperature: -10 to +45 ° C (+14 to 113 ° F)
- Storage temperature: -30 to 70
- Support PoE power supply (IEEE 802.3af), class 2
- Power adapter (optional): AC 100-240V

- input, DC 5V/2A output
- USB output current: 5V/500mA
 - Power consumption (PSU): 1.30 W-1.48 W
 - Power consumption (PoE): 1.368 W-1.832 W
 - Dimension (W*D*H*T): 209.0 mm*167.5 mm*214.8 mm*53.4 mm

Package Features

- Package content:
 - - Yealink T73W IP phone
 - - Handset with handset cord
 - - Ethernet Cable (2m CAT5E UTP Cable)
 - - Stand
 - - Quick Start Guide
 - - Power Adapter (Optional)
 - - Wall Mount Bracket (Optional)
- Qty/CTN: 5 PCS
- N.W/CTN: 5.554 kg
- G.W/CTN: 6.126 kg
- Giftbox size: 231 mm*237 mm*102 mm
- Carton Meas: 530 mm*243 mm*247 mm

Compliance

